March 23, 2010

RE: Grace Waterproofing and Air Barrier Materials LEED 2009 Green Building Rating System™

To Whom It May Concern:

This letter will detail the contribution of Grace Waterproofing and Air Barrier materials to the LEED 2009 Green Building Rating System[™] for New Construction, Major Renovations of existing buildings, Core & Shell and Schools.

MR Credit 2.1: Construction Waste Management, Divert 50% from Disposal MR Credit 2.2: Construction Waste Management, Divert 75% from Disposal

In areas where facilities exist, the following Grace Waterproofing and Air Barrier materials are recyclable and can contribute to earning Materials and Resources Credit 2.1 and Credit 2.2.

•	Wooden Pallet	wood	45 lbs
•	Sheet core	cardboard	3 lbs/core
•	Carton	cardboard	4 lbs/carton
•	Pail	steel	2 lbs/pail
•	Pail	HDPE (plastic)	2 lbs/pail
•	Drum	steel	29 lbs/drum
•	Drum	fiber	12 lbs/drum

MR Credit 4.1: Recycled Content, 10% MR Credit 4.2: Recycled Content, 20%

The recycled content of Grace Waterproofing and Air Barrier materials is as follows and can contribute to earning Materials and Resources Credit 4.1 and Credit 4.2. All other Grace Waterproofing and Air Barrier materials not listed below do not contain recycled content, 0% Post Consumer and 0% Post Industrial.

	Wt. Percent	Wt. Percent
	Post Industrial	Post Consumer
Grace Product	Recycled Content	Recycled Content
Hydroduct® 200	89%	0%
Hydroduct® 220	86%	0%
Hydroduct® 225	83%	0%
Hydroduct® 660	83%	0%
HydroCoil® 600	92%	0%

MR Credit 5.1: Regional Materials, 10% Extracted, Processed & Manufactured Regionally MR Credit 5.2: Regional Materials, 20% Extracted, Processed & Manufactured Regionally

Grace Waterproofing and Air Barrier materials are manufactured in several locations in North America. If these locations fall within a 500-mile radius of the project site and the location the raw materials used to make the finished product are extracted, recovered or harvested within a 500-mile radius of the project, then these materials or a portion of the materials can contribute to earning Materials and Resources Credit 5.1 and Credit 5.2.

The following are the locations of the Grace Waterproofing and Air Barrier materials manufacturing plants:

<u>Plant Location</u> <u>Product</u>

Bedford Park, IL Perm-A-Barrier Products except Perm-A-Barrier VPS, Procor materials,

and Bituthene materials

Mount Pleasant, TN Bituthene materials, Preprufe materials and Florprufe materials

Newburyport, MA Perm-A-Barrier VPS
Union County, NC All Hydroduct materials

Please contact your local Grace Representative to request a project specific letter pertaining to Credit 5.1 and Credit 5.2. The letter will provide the quantity of raw materials that are extracted, recovered or harvested within 500 miles of the project location.

MR Credit 6: Rapidly Renewable Materials

None of the Grace Waterproofing and Air Barrier materials are made from or contain any rapidly renewable materials.

MR Credit 7: Certified Wood

None of the Grace Waterproofing and Air Barrier materials are made from or contain any wood-based materials. MR Credit 7 is not applicable to Grace Waterproofing and Air Barrier materials.

EQ Credit 4.2: Low Emitting Materials, Paints & Coatings

EQ Credit 4.2 pertains to products that are to be used in the interior of a building. Grace Waterproofing and Air Barrier materials are applied onto the exterior of a structure and therefore would not contribute to this credit. However, Grace has provided the volatile organic content (VOC) of Grace Waterproofing and Air Barrier materials listed below.

Grace Product

Perm-A-Barrier Liquid (Part A and B)

VOC Content g/L

75 (as applied)

Perm-A-Barrier WB Primer 10 Perm-A-Barrier VP 20

Procor (all types) 75 (as applied)
Perm-A-Barrier Primer Plus Less than 1

Please feel free to contact me with any additional questions or information.

Sincerely,

John Dalton

Grace Technical Services Manager

Polo Detton

