

Material Safety Data Sheet May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.		U.S. DEPARTMENT OF LABOR Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072	
Identity (As Used on Label and List) <b>Pyrok Acoustement Plaster 20</b>		<b>Note:</b> Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.	
<b>SECTION I</b>			
Manufacturer's Name <b>Pyrok, Inc.</b>		Emergency Telephone Number <b>914-777-7070</b>	
Address (Number, Street, City, State and Zip Code) <b>400 Colony Square – 1630</b>		Telephone Number for Information <b>404-607-9765</b>	
<b>Atlanta, GA 30361</b>		Date Prepared <b>Revised 06/01/98</b> Signature of Preparer (optional)	
<b>SECTION II – Hazardous Ingredients/ Identity Information</b>			
Hazardous Components (Specific Chemical Identity: Common Name (s))		OSHA PEL	ACGIH TLV
		Other Limit Recommended	% (optional)
<b>Gypsum Plaster CAS #7778-18-9</b>		<b>5-15mg/M</b>	<b>10mg/M</b>
<b>SECTION III – Physical/Chemical Characteristics</b>			
Boiling Point	<b>N/A</b>	Specific Gravity (H <sub>2</sub> O=1)	
Vapor Pressure (mm Hg)	<b>N/A</b>	Melting Point	
Vapor Density (AIR=1)	<b>N/A</b>	Evaporation Rate (Butyl Acetate = 1)	
<b>Solubility in Water</b>	<b>Yes</b>	<b>Wet density Avg.</b>	<b>69.5 pcf</b>
Appearance and Odor <b>Grey, slurry and odorless</b>			
<b>SECTION IV – Fire and Explosion Hazard Data</b>			
Flash Point (Method Used)	Flammable Limits	LEL	UEL
<b>None</b>	<b>None</b>		
EXTINGUISHING MEDIA <b>N/A</b>			
Special Fire Fighting Procedures			
<b>Totally incombustible, tested by UNDERWRITERS LABORATORIES</b>			
Unusual Fire and Explosion Hazards <b>None</b>			

<b>SECTION V – Reactivity Data</b>			
Stability	Unstable		Conditions to Avoid
	Stable	<b>Yes</b>	
Incompatibility (Materials to Avoid)			

<b>SECTION V – Reactivity Data</b>			
Stability	Unstable		Conditions to Avoid
	Stable	<b>Yes</b>	
Incompatibility (Materials to Avoid)			
Hazardous Decomposition or Byproducts			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	<b>X</b>	
<b>SECTION VI – Health Hazard Data</b>			
Route (s) of Entry:	Inhalation?	Skin?	Ingestion?
	<b>Yes</b>	<b>No</b>	<b>No</b>
Health Hazards (Acute and Chronic)			
<b>Acute: Irritation of mucous membranes</b>			
<b>Chronic: Chronic bronchitis</b>			
Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	<b>No</b>	<b>No</b>	<b>No</b>
Signs and Symptoms of Exposure			
<b>Irritation of eyes, nose, cough, labored breathing</b>			
Medical Conditions			
Generally Aggravated by Exposure			
<b>Breathing and lung disorders</b>			
Emergency and First Aid Procedures			
<b>Rinse with clean water if eye contact. Move person to area with fresh air. Get medical attention immediately.</b>			
<b>SECTION VII – Precautions for Safe Handling and Use</b>			
Steps to Be Taken in Case Material is Released or Spilled			
<b>No special steps required. Clean up with clean water</b>			
Waste Disposal Method			
<b>Treat like all cementitious waste disposal methods</b>			
Precautions to Be Taken in Handling and Storing			
<b>Dust masks should be worn when handling this product and other products generating air born dust.</b>			
Other Precautions			
<b>Post “Slippery When Wet” signs where appropriate</b>			
<b>SECTION VIII – Control Measures</b>			
Respiratory Protection ( <i>Specify Type</i> )			
<b>Normal dust masks</b>			
Ventilation			
<b>Exhaust fans may be necessary when mixing in enclosed areas</b>			
Protective Gloves <b>Vinyl or rubber gloves</b>	Mechanical (General)	<b>Exhaust fans may be necessary when mixing in enclosed areas</b>	Other <b>Moving air</b>
			Other
Other Protective Clothing or Equipment		Eye Protection	
<b>None</b>		<b>Safety glasses</b>	
Work/Hygienic Practices			
<b>Minimize dust release when opening and pouring bagged product</b>			
Work/Hygienic Practices			