

<b>Material Safety Data Sheet</b> May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.		<b>U.S. DEPARTMENT OF LABOR</b> Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072	
Identity (As Used on Label and List) <b>Pyrok Acoustement Plaster 40</b>		<i>Note:</i> Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.	
<b>SECTION I</b>			
Manufacturer's Name <b>Pyrok, Inc.</b>		Emergency Telephone Number <b>914-777-7070</b>	
Address (Number, Street, City, State and Zip Code) <b>1201 Peachtree Street</b> <b>400 Colony Square – Suite 1630</b> <b>Atlanta, GA 30361</b>		Telephone Number for Information <b>404-607-9765</b> Date Prepared Revised 6/01/98 Signature of Preparer (optional)	
<b>SECTION II – Hazardous Ingredients/ Identity Information</b>			
Hazardous Components (Specific Chemical Identity: Common Name (s))		OSHA PEL	ACGIH TLV
		Other Limit Recommended	% (optional)
<b>Gypsum Plaster CAS #7778-18-9</b>		<b>5-15 mg/M 3</b>	<b>10 mg/M3</b>
<b>SECTION III – Physical/Chemical Characteristics</b>			
Boiling Point	<b>N/A</b>	Specific Gravity (H <sub>2</sub> O=1)	
Vapor Pressure (mm Hg)	<b>N/A</b>	Melting Point	
Vapor Density (AIR=1)	<b>N/A</b>	Evaporation Rate (Butyl Acetate = 1)	
Solubility in Water	<b>Yes</b>	<b>Wet Density Av.</b>	<b>69.5 Pcf</b>
Appearance and Odor	<b>Grey Slurry and Odorless</b>		
<b>SECTION IV – Fire and Explosion Hazard Data</b>			
Flash Point (Method Used)	Flammable Limits	LEL	UEL
<b>None</b>	<b>None</b>		
EXTINGUISHING MEDIA			
<b>N/A</b>			
Special Fire Fighting Procedures			
<b>Totally incombustible, tested by UNDERWRITERS LABORATORIES</b>			
Unusual Fire and Explosion Hazards			
<b>None</b>			

(reproduced)

<b>SECTION V – Reactivity Data</b>			
Stability	Unstable		Conditions to Avoid
	Stable	<b>Yes</b>	
Incompatibility (Materials to Avoid)			
Hazardous Decomposition or Byproducts			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	<b>X</b>	
<b>SECTION VI – Health Hazard Data</b>			
Route (s) of Entry:	Inhalation?	Skin?	Ingestion?
	<b>Yes</b>	<b>No</b>	<b>No</b>
Health Hazards (Acute and Chronic)			
<b>Acute: Irritation of mucous membranes</b>			
<b>Chronic: Chronic bronchitis</b>			
Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	<b>No</b>	<b>No</b>	<b>No</b>
Signs and Symptoms of Exposure			
<b>Irritation of eyes, nose, cough, labored breathing</b>			
Medical Conditions			
Generally Aggravated by Exposure			
<b>Breathing and lung disorders</b>			
Emergency and First Aid Procedures			
<b>Rinse with clean water if eye contact. Move person to area with fresh air. Get medical attention immediately.</b>			
<b>SECTION VII – Precautions for Safe Handling and Use</b>			
Steps to Be Taken in Case Material is Released or Spilled			
<b>No special steps required. Clean up with clean water</b>			
Waste Disposal Method			
<b>Treat like all cementitious waste disposal methods</b>			
Precautions to Be Taken in Handling and Storing			
<b>Dust masks should be worn when handling this product and other products generating air born dust.</b>			
Other Precautions			
<b>Post “Slippery When Wet” signs where appropriate</b>			
<b>SECTION VIII – Control Measures</b>			
Respiratory Protection ( <i>Specify Type</i> )			
<b>Normal dust masks</b>			
Ventilation			
<b>Exhaust fans may be necessary when mixing in enclosed areas</b>			
Protective Gloves <b>Vinyl or rubber gloves</b>	Mechanical (General)	<b>Exhaust fans may be necessary when mixing in enclosed areas</b>	Other <b>Moving air</b>
			Other
Other Protective Clothing or Equipment		Eye Protection	
<b>None</b>		<b>Safety glasses</b>	
Work/Hygienic Practices			
<b>Minimize dust release when opening and pouring bagged product</b>			
Work/Hygienic Practices			